



TS-h1887XU-RP-E2334-16G		
CPU Intel® Xeon® E-2334 4C 8T 3.4GHz, up to 4.8GHz		
CPU Architecture 64-bit x86		
Floating Point Unit Yes		
Encryption Engine Yes (AES-NI)		
System Memory 16 GB ECC DDR4 (1 x 16 GB)		
Maximum Memory 128GB (4 x 32 GB)		
Memory Slot 4 x ECC UDIMM DDR4		
Flash Memory 5GB (Dual boot OS protection)		
Drive Bay 18 (12 x 3.5-inch SATA + 6 x 2.5-inch SATA)		
Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 2.5-inch bays:		
2.5-inch SATA solid state drives		
M.2 Slot Optional via a QM2 PCIe adapter		
SSD Cache Acceleration Yes Support		
GPU pass-through Yes		
2.5 Gigabit Ethernet Port 2 (2.5G/1G/100M) (2.5G/1G/100M)		
10 Gigabit Ethernet Port 2 x 10GBASE-T (10G/5G/2,5G/1G/100M)		
PCIe Slot 3 (2 x Gen4 x4 +1 x Gen 4 x8)		
USB 3.2 Gen 2 (10Gbps) 4 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps Port		
Form Factor 2U Rackmount		

LED Indicators	Status (Green/Red) LAN (Green) USB (Blue) HDD status (Green/Red)
Buttons	Power, Reset
Dimensions (HxWxD)	88 × 483 × 630 mm
Weight (Net)	13 kg
Weight (Gross)	19 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	2 x 550W CRPS PSU
Fan	4 x 60mm, 12VDC

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.